Villager 5 Duo









| Code | V5-DUO |
|-----------------|--------|
| Output | 5kW |
| Log length | 325mm |
| Nett efficiency | 83.7% |
| Width | 463mm |
| Height | 566mm |
| Depth | 367mm |

The Villager Duo range boasts modern technology and efficiencies hidden behind its grand exterior. Certain to bring character to any room with its ash lip, large glass viewing area and solid controls, it will become a gathering point during the colder Winter months.

Features

Lifetime guarantee
Preheated airwash system for clean glass
Stainless steel ash pan
Burns wood or solid fuel
Primary and secondary burn to improve efficiency
Top or rear flue outlet

Optional Extras

Add-in Boiler - [AIB11] Arada Ash Carrier - Large - [ARA018] Arada Universal Stand - [STAND001] Universal Stand/Log Store - [STAND003]



Villager 5 Duo - Technical Information


| Code | V5-DUO |
|-------------------------------------|--------|
| Output range | 1-6kW |
| Nett efficiency | 83.7 % |
| Refuelling period | 1 hour |
| Width | 463mm |
| Height | 566mm |
| Depth | 367mm |
| Height to centre of rear flue | 458mm |
| Depth of back to centre of top flue | 120mm |
| Flue diameter | 127mm |
| Suitable for 12mm hearth | Yes |
| Under hearth temperature | 61.6°C |
| Suitable for direct air supply kit | No |
| Packed weight | 76kg |
| Maximum log length | 325mm |

Minimum Distance To Combustibles

Distance C

| To rear of stove | 975 mm |
|-----------------------------|--------|
| To sides of stove | 750 mm |
| Above stove | 381 mm |
| Boiler Tapping Measurements | |
| Distance A | 257 mm |
| Distance B | 315 mm |

312 mm



Add In Boiler Tapping Measurements. Rear view example shown. Not to scale.